

ShopPro 25 DRUM SANDER



SuperMax
Tools

EXCEPTIONAL SUPERMAX FEATURES

- ▶ **INTELLISAND Technology:** Automatically adjusts conveyor speed based on load
 - Prevents gouging, damaging or burning stock
 - Provides consistent finish even with varying grain pattern and density
 - Greatly increases abrasive planing and dimensioning speed
- ▶ **Flatness Guarantee:** Precision-flattened steel conveyor bed reinforced with four steel cross sections for no "flex" in conveyor, guaranteeing flatness to less than .010" across the width of the sander
- ▶ **Abrasive conveyor belt** offers the best grip for raw wood, giving you the ability to accommodate stock that is much shorter or thinner
- ▶ **Patented Abrasive Attachment System** effectively tensions the abrasive wraps, preventing loose abrasive and overlap
- ▶ **Easiest access** to abrasive fastening system of any drum sander! Machine design includes additional space around abrasive, eliminating the need for special tools.
- ▶ **Self-cooling drum** prevents overheating and extends abrasive life

ADDITIONAL FEATURES

- ▶ Height adjustment handle makes both large height changes and minute adjustments for extremely precise sanding thickness control (3/32" per turn height adjustment)
- ▶ Tension rollers are adjustable in height and hold down pressure, eliminating snipe
- ▶ Cast stand, zinc-plate steel bed, centerless ground column tubes
- ▶ Shipped assembled, no assembly required



Shown with optional accessories

Item#	Description	Price
925002	ShopPro 25 Drum Sander	\$1,875.00

Optional Accessories

59120	Abrasive Cleaning Stick	\$8.00
98-0070	Rack-n-Roll Abrasive Storage Shelf	\$45.00
98-0118	Digital Depth Gauge	\$400.00
98-0130	Caster Wheels (4)	\$89.00
98-2201	Infeed/Outfeed Tables, 10"D x 24"W	\$99.00
Specify	Pre-Cut Abrasive Rolls, 36-220 grit (specify), three (3) wraps per box	\$29.95
Specify	Pre-Marked Abrasive Rolls, aluminum oxide, 36-220 grit (specify)	\$129.00
Specify	Pre-Marked Abrasive Rolls, zirconium* 24-120 grit (specify)	\$199.00

* 2-5x longer life vs. aluminum oxide

Sanding Capacity:

Maximum Width (in):	25
Minimum Length (in):	2 1/4
Maximum Thickness (in):	4
Minimum Thickness (in):	1/32
Dimensions H x W x D (in):	43 x 46 x 31
Drum (in):	5 x 25 extruded aluminum
Dust Hood:	Steel hood with one 4" vacuum port, hinged at back, min. 600 CFM recommended
Ball Bearings (1"):	2, sealed and permanently lubricated
Conveyor Motor :	43 in.-lb. torque, direct drive D.C. motor, infinitely variable 0-10 FPM
Drive Motor (TEFC):	1 3/4 HP
Power Requirements:	110-120V, 60 Hz
Shipping Weight (lbs):	325